

# Lightology

lightology.com  
866-954-4489  
02-10-26

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG50986**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Stratus Indoor LED Linear Wall Grazer

By PureEdge Lighting



### Description

The Stratus Linear Indoor Wall Grazer is a Non-IC rated fixture designed for use in recessed cove or surface mount applications for new residential, new commercial, and remodel. Lights textured walls up to 30 feet high. Mounts flush to ceilings or recessed within a pocket cove for the most dramatic effect. Available in 1 foot and 4 foot lengths in 3000K or 4200K color temperature. Link multiple Stratus fixtures to create long runs. Included components: Wall mounting bracket, housing, joiner bracket, reflector, LED panel, one internal 0-10V power supply, and louver. Note: End caps sold separately. Feed fixture with 120-277VAC. Dimmable with a 0-10V dimmer, sold separately. For indoor dry locations. Product is built to order.

### Specifications

COLOR . . . . . N/A  
BODY FINISH . . . . . Aluminum  
WATTAGE . . . . . 15W  
DIMMER . . . . . 0-10V  
DIMENSIONS . . . . . 12"L x 5.64"H x 5.5"D  
INTEGRATED LED MODULE . . . . . 1 x LED/15W/120-277V LED

### Technical Information

LAMP LIFE . . . . . 50000 hours  
COLOR RENDERING . . . . . 90 CRI  
LAMP COLOR . . . . . 3000K  
LUMENS/WATT . . . . . 55.47  
LUMINOUS FLUX . . . . . 832 lumens




Shown in aluminum



**INCLUDED COMPONENTS**  
Wall mounting bracket, Housing, Joiner Bracket, Reflector,  
LED Panel, Power Supply, and Louver.

**ACCESSORIES**  
End Cap

**INCLUDED COMPONENTS**



**A. WALL MOUNTING BRACKET**  
For all types of mounting conditions from recessed, open  
commercial, and outdoor.

**B. LED HOUSING**  
For 12" and 48" fixture lengths.

**C. LED HOUSING**  
For 12" and 48" fixture lengths.

**D. JOINER BRACKET**  
Joiner bracket for linking fixtures.

**E. LED REFLECTOR**  
For recessed and open applications.

**F. LED REFLECTOR**  
For recessed and open applications.

**G. LED PANEL**  
Integrated LED panel, 15W, 3000K, or 4200K.

**H. LED PANEL**  
Integrated LED panel, 15W, 3000K, or 4200K.

**I. END CAP**  
End cap for fixture.



CLICK TO VIEW PRODUCT

Notes: