

lightology.com 866-954-4489 09-14-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN52455	
Approved On:	Approved By:

IC25R 5 Inch IC Shallow Remodel Housing By Juno Lighting

Description

IC25R 5 Inch Shallow Universal IC Remodel Housing is an energy efficient sealed housing. IC remodel housing for remodel application where back side of ceiling is not accessible. Installs through an opening in the ceiling from below. Secured in place by factory installed remodel springs. Can be completely covered with insulation. Accommodates ceilings up to 1 1/8 inch thick. When used with Air-Loc gasket (ALG5R), stops infiltration and ex-filtration of air, reducing heating and cooling costs. Trims shown with Air-Loc symbol do not require a gasket. One 120 volt, A19, BR30, PAR30, PAR20, R20 or PAR30L medium base halogen/incandescent lamp or LED equivalent is required, but not included. Lamp type and wattage dependent upon housing/trim combination (see attached Juno manufacturer specification). Incandescent/halogen dimmable with a standard incandescent dimmer. Consult lamp manufacturer for dimmer compatibility when using an LED equivalent lamp. UL listed for throughbranch wiring, damp locations and IP. Product thermally protected against improper use of lamps. Trim 212N is wet location approved for covered ceiling applications. 12.5 inch length x 5.9 inch width x 5.75 inch height. A complete fixture includes a housing and trim, sold separately.

Specifications

REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
BULB NOT INCLUDED PAR30L/Medium (E26)/120V Halogen
OTHER BULB OPTIONS
1 x PAR20/Medium (E26)/120V Halogen


1 x PAR20/Medium (E26)/120V LED 1 x PAR30S/Medium (E26)/120V Halogen 1 x PAR30S/Medium (E26)/120V LED 1 x R20/Medium (E26)/120V Incandescent 1 x R20/Medium (E26)/120V LED

Technical Information

PRODUCT DIMENSIONS
HOUSING HEIGHT
HOUSING TYPE
CEILING TYPE



Shown in aluminum



5 1/2" CEILING CUTOUT



CLICK TO VIEW PRODUCT