

lightology.com 866-954-4489 10-16-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN534237	
Approved On:	Approved By:

MD1LG2 Square Mini LED Downlight Housing and Trim By Juno Lighting





Description

The MD1LG2 Series Square Mini LED Downlight opens up a multitude of task and accent lighting possibilities, especially when installation space is at a premium. Ideal for both residential and commercial limited space applications including niches, bookshelves, displays and cabinets. These second generation recessed Mini LEDs still require only 5 watt input, but now feature 50 percent higher lumens. Available in White and Black painted finish and Satin Nickel or Bronze plated finish. Includes 5 watts LED with choice of 2700K, 3000K, 3500K or 4000K color temperature, 80+CRI, 300 lumens, and Spot (16 degree), Narrow Flood (24 degree), and Flood (35 degree) beam angle optic. Comparable light output to a 20 watt MR11 halogen. 50,000 hour average lamp life. Designed for use in IC (insulated ceiling) or Non-IC construction. If using in an IC application, it is recommended that the insulation be pulled away from the fixture due to adjustment feature. Includes 12 volt onboard LED driver, but requires a remote Class II electronic transformer (recommended Juno TL602E low voltage electronic transformer) to complete the system, sold separately. UL listed for damp locations. 2.25 inch square trim x 2.9 inch height. May be dimmed using the following Juno qualified dimmers: Leviton Acenti Ace-06-1L, Lutron Diva DVELV-300P, Lutron Nova T NTELV300, Lutron Skylark SELV-300P, or Lutron Spacer SPSELV-600, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

APERTURE SIZE
APERTURE SHAPE
HOUSING HEIGHT
HOUSING TYPE
CEILING TYPE
FUNCTION
LAMP LIFE
BEAM ANGLE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX



Shown in white





CLICK TO VIEW PRODUCT

Notes:		