

# Lightology

lightology.com  
866-954-4489  
06-29-26

Project: \_\_\_\_\_

Company: \_\_\_\_\_

Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_

SPEC #: **WAC537713**

Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Low Voltage 4 inch New Construction NIC Housing By WAC Lighting



### Description

Low Voltage 4 Inch New Construction Non-IC Housing is 20 gauge galvanized steel and includes an electronic transformer. Non-IC designation requires a minimum 3 inch clearance on all sides of housing when insulation is present. Suitable for shallow joist installation. Ceiling cutout: 4 9/16 inch. Requires one 12 volt GU5.3 MR16 halogen or LED HR and 84 series 4 inch trim. A complete fixture includes a housing and trim, sold separately.

### Specifications



REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Steel
WATTAGE	7W
DIMMER	Low Voltage Electronic
DIMENSIONS	14.5"L x 4.31"W x 4.25"H
BULB NOT INCLUDED	1 x MR16/GU5.3 (bipin)/7W/12V LED
COUNTRY OF ORIGIN	China

### Technical Information

APERTURE SIZE	4.500"
APERTURE SHAPE	Round
HOUSING HEIGHT	4"
HOUSING TYPE	New Construction NON IC
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight



Shown in steel



CLICK TO VIEW PRODUCT

Notes: