

lightology.com 866-954-4489 12-28-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN538353	
Approved On:	Approved By:

Aculux 3.25 Inch Round 2000LM LED 35Deg IC Housing 80CRI By Juno Lighting





Description

The Aculux IC420 3.25 Inch 2000 Lumen IC New Construction Luminaire with 35 degree beam angle has 45 degree visual cutoff and features precision Acu-Aim geared hot-aiming. Compatible with downlight, adjustable and wall wash trims. IC housings are rated for direct contact with insulation Available in 2700K, 3000K, 3500K or 4000K color temperatures, 80CRI, with modular field interchangeable optics of 12 degree Spot, 24 degree Narrow Flood, 35 degree Flood, and 50 degree Wide Flood, 120 volt. LED driver field replaceable from above or below the ceiling. 50,000 hour lamp life rated at 70 percent lumen maintenance. Optional optical accessories sold separately. Trim styles include: Trim Ring, Self-Flanged and Flush Mount reflectors, sold separately. For flush mount installations in drywall ceiling, use the FMA4 flush mount adapter, sold separately. Accommodates up to three additional beam control lenses or filters, sold separately. UL and cUL listed for through branch wiring and damp locations. Wet location listed with certain trims. Energy Star qualified with select trims. 5 year warranty. 19.63 inch width x 13.75 inch depth x 8.94 inch height. See attached manufacturer dimmer compatibility reference for compatible dimmers with a 120 volt driver. A complete fixture includes a housing and trim, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR
BODY FINISH
WATTAGE
DIMMER Dimmable
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

HOUSING HEIGHT
HOUSING TYPE
CEILING TYPE
LAMP LIFE
BEAM ANGLE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX



Shown in black





CLICK TO VIEW PRODUCT

Notes:			