

lightology.com 866-954-4489 08-30-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN538606	
Approved On:	Approved By:

Aculux 3.25 Inch Square 2000LM 24Deg Low Profile 90CRI By Juno Lighting





Description

The Aculux TC420LPSQ 3.25 Inch 2000 Lumen Low Profile Recessed LED Non-IC Luminaire with 24 degree beam angle has 45 degree visual cutoff and features precision Acu-Aim geared hot-aiming. Compatible with downlight, adjustable and wall wash trims. Non-IC luminaires must be used in non-insulated areas or where insulation is spaced at least 3 inches from housing. Available in 2700K or 3000K color temperatures, 90CRI, with modular field interchangeable optics of 12 degree Spot, 24 degree Narrow Flood, 35 degree Flood, and 50 degree Wide Flood, 120 volt. LED driver field replaceable from above or below the ceiling. 50,000 hour lamp life rated at 70 percent lumen maintenance. Optional optical accessories sold separately. Trim styles include: Trim Ring, Self-Flanged and Flush Mount reflectors, sold separately. For flush mount installations in drywall ceiling, use the FMA4 flush mount adapter, sold separately. UL and cUL listed for through branch wiring and damp locations. Wet location listed with certain trims. Energy Star qualified with select trims. 5 year warranty. 19.63 inch width x 13.75 inch depth x 4 inch height. See attached manufacturer dimmer compatibility reference for compatible dimmers with a 120 volt driver. A complete fixture includes a housing and trim, sold separately.

Specifications

Technical Information
INTEGRATED LED MODULE
DIMENSIONS
DIMMER Dimmable
WATTAGE
BODY FINISH
REFLECTOR/BAFFLE COLOR

HOUSING HEIGHT
HOUSING TYPE New Construction NON IC
CEILING TYPE Drywall with Trim
LAMP LIFE
BEAM ANGLE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX



Shown in black





CLICK TO VIEW PRODUCT

Notes:	