

Lightology

lightology.com
866-954-4489
08-30-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **JUN538913**
Approved On: _____ Approved By: _____

Aculux 3.25 Inch 2000LM 35Deg Non-IC Housing 90CRI

By Juno Lighting



Description

The Aculux TC420L 3.25 Inch 2000 Lumen Recessed Adjustable LED Non-IC Luminaire has 45 degree visual cutoff and features precision Acu-Aim geared hot-aiming. Non-IC luminaires must be used in non-insulated areas or where insulation is spaced at least 3 inches from housing. Available in 2700K or 3000K color temperatures, 90CRI, with modular field interchangeable optics of 12 degree Spot, 24 degree Narrow Flood, 35 degree Flood, and 50 degree Wide Flood, 120 volt. LED driver field replaceable from above or below the ceiling. 50,000 hour lamp life rated at 70 percent lumen maintenance. Optional optical accessories sold separately. Trim styles include: Trim Ring, Self-Flanged and Flush Mount reflectors, sold separately. For flush mount installations in drywall ceiling, use the FMA4 flush mount adapter, sold separately. UL and cUL listed for through branch wiring and damp locations. Wet location listed with certain trims. Energy Star qualified with select trims. 5 year warranty. 18 inch width x 13.75 inch depth x 5.44 inch height. See attached manufacturer dimmer compatibility reference for compatible dimmers. A complete fixture includes a housing and trim, sold separately.

Specifications


REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Black
WATTAGE 27W
DIMMER Dimmable
DIMENSIONS 18"W x 5.44"H x 13.75"D
INTEGRATED LED MODULE 1 x LED/27W/120V LED

Technical Information

APERTURE SIZE 3.250"
HOUSING HEIGHT 6"
HOUSING TYPE New Construction NON IC
CEILING TYPE Drywall with Trim
LAMP LIFE 50000 hours
BEAM ANGLE 35°
COLOR RENDERING 90 CRI
LAMP COLOR 2700K
LUMENS/WATT 74.07
LUMINOUS FLUX 2000 lumens



Shown in black



CLICK TO VIEW PRODUCT

Notes: