

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: JUN538920	
Approved On:	Approved By:

Aculux 3.25 Inch 2000LM 12Deg Chicago Plenum 80CRI By Juno Lighting





Description

The Aculux TC420L Chicago Plenum 3.25 Inch 2000 Lumen Recessed Adjustable LED Non-IC Luminaire has 45 degree visual cutoff and features precision Acu-Aim geared hot-aiming. Non-IC luminaires must be used in non-insulated areas or where insulation is spaced at least 3 inches from housing. Available in 2700K, 3000K, 3500K or 4000K color temperatures, 80CRI, with modular field interchangeable optics of 12 degree Spot, 24 degree Narrow Flood, 35 degree Flood, and 50 degree Wide Flood, 120 volt. LED driver field replaceable from above or below the ceiling. 50,000 hour lamp life rated at 70 percent lumen maintenance. Optional optical accessories sold separately. Trim styles include: Trim Ring, Self-Flanged and Flush Mount reflectors, sold separately. For flush mount installations in drywall ceiling, use the FMA4 flush mount adapter, sold separately. UL and cUL listed for through branch wiring and damp locations. Wet location listed with certain trims. Energy Star qualified with select trims. 5 year warranty. 18 inch width x 13.75 inch depth x 5.44 inch height. See attached manufacturer dimmer compatibility reference for compatible dimmers. A complete fixture includes a housing and trim, sold separately.

Specifications

BODY FINISH					
WATTAGE					
DIMMER Dimmable					
DIMENSIONS					
INTEGRATED LED MODULE					
Technical Information					
Technical Information					
Technical Information HOUSING HEIGHT					
HOUSING HEIGHT 6"					

 BEAM ANGLE
 12°

 COLOR RENDERING
 80 CRI


 LAMP COLOR
 2700K

 LUMENS/WATT
 74.07

 LUMINOUS FLUX
 2000 lumens



Shown in black





CLICK TO VIEW PRODUCT

Notes:		