

Lightology

lightology.com
866-954-4489
04-28-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EU543222**
 Approved On: _____ Approved By: _____

Amigo 3IN RD Trimless Adjustable Gimbal / Remodel Housing By Eurofase



Description

The Amigo 28716 3 Inch Round Aperture Non-IC Remodel Housing with Gimbal Trimless is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes steel mesh plate with perforated perimeter to allow mud to bond to mounting surface leaving a seamless finish in the ceiling. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 3000K or 3500K color temperature, 80+CRI, 1290 lumens. 30 degree tilt. 50,000 hour average lamp life. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC dimmer, sold separately. Cutout: 3 inch round. Can be converted to a Non-IC new construction housing using the 30537-019 mounting plate.

Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	15W
DIMMER	Standard 120V
DIMENSIONS	2.75"W x 5.75"H
INTEGRATED LED MODULE	1 x LED/15W/120V LED
COUNTRY OF ORIGIN	China

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Round
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	80 CRI
LAMP COLOR	3000K
LUMENS/WATT	86.00
LUMINOUS FLUX	1290 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: