

Lightology

lightology.com
866-954-4489
05-24-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EU543227**
 Approved On: _____ Approved By: _____

Amigo 3 inch Square Trimless Downlight / Remodel Housing By Eurofase



Description

The 28717 3 Inch Square Aperture Non-IC Remodel Housing with Downlight Trimless is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes steel mesh plate with perforated perimeter to allow mud to bond to mounting surface leaving a seamless finish in the ceiling. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 3000K or 3500K color temperature, 80+CRI, 1290 lumens. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC dimmer, sold separately. ETL listed. Cutout: 3 inch square.

Specifications


| | |
|------------------------|--------------------------|
| REFLECTOR/BAFFLE COLOR | N/A |
| BODY FINISH | Black |
| WATTAGE | 15W |
| DIMMER | Low Voltage Electronic |
| DIMENSIONS | 2.75"W x 5.75"H x 2.75"D |
| INTEGRATED LED MODULE | 1 x LED/15W/120-277V LED |
| COUNTRY OF ORIGIN | China |

Technical Information

| | |
|-----------------|------------------------|
| APERTURE SIZE | 3.000" |
| APERTURE SHAPE | Square |
| HOUSING HEIGHT | 6" |
| HOUSING TYPE | Remodel NON IC |
| CEILING TYPE | Drywall Trimless/Flush |
| FUNCTION | Downlight |
| LAMP LIFE | 50000 hours |
| BEAM ANGLE | 40° |
| COLOR RENDERING | 90 CRI |
| LAMP COLOR | 3000K |
| LUMENS/WATT | 86.00 |
| LUMINOUS FLUX | 1290 lumens |



Shown in black



CLICK TO VIEW PRODUCT

Notes: