Lightology

lightology.com
866-954-4489
11-09-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EUF543227**

Approved On: Approved By:

Amigo 3 inch Square Trimless Downlight / Remodel Housing


By Eurofase


Description

The 28717 3 Inch Square Aperture Non-IC Remodel Housing with Downlight Trimless is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes steel mesh plate with perforated perimeter to allow mud to bond to mounting surface leaving a seamless finish in the ceiling. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 3000K or 3500K color temperature, 80+CRI, 1290 lumens. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC dimmer, sold separately. ETL listed. Cutout: 3 inch square.



Shown in black







Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	2.75"W x 5.75"H x 2.75"D
INTEGRATED LED MODULE	1 x LED/15W/120-277V LED
COUNTRY OF ORIGIN	China

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	86.00
LUMINOUS FLUX	1290 lumens

CLICK TO VIEW PRODUCT

Notes: