



**BRAND**

Eurofase

**DESCRIPTION**

The Amigo 28718 3 Inch Square Aperture Non-IC Remodel Housing with Gimbal Trimless is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes steel mesh plate with perforated perimeter to allow mud to bond to mounting surface leaving a seamless finish in the ceiling. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 3000K or 3500K color temperature, 80+CRI, 1290 lumens. 30 degree tilt. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC dimmer, sold separately. Cutout: 3 inch square. Can be converted to a Non-IC new construction housing using the 30536-012 mounting plate.





Shown in: White

<b>TRIM COLOR</b>	N/A
<b>BODY FINISH</b>	White
<b>WATTAGE</b>	15W
<b>DIMMER</b>	Standard 120V
<b>DIMENSIONS</b>	2.75"W x 5.75"H x 2.75"D
<b>LED MODULE INCLUDED</b>	
<b>LAMP</b>	1 x LED/15W/120V LED

*Technical Information*

<b>LUMINOUS FLUX</b>	1290 lumens
<b>LUMENS/WATT</b>	86.00
<b>LAMP COLOR</b>	3000 K
<b>COLOR RENDERING</b>	80 CRI
<b>BEAM ANGLE</b>	40°
<b>LAMP LIFE</b>	50000 hours
<b>FUNCTION</b>	Adjustable Accent
<b>CEILING TYPE</b>	Drywall Trimless/Flush
<b>HOUSING TYPE</b>	Remodel NON IC
<b>HOUSING HEIGHT</b>	6"
<b>ITEM NUMBER</b>	EUF543230



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE