

# Lightology

lightology.com  
866-954-4489  
06-10-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **EUF543235**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Amigo 3 inch Round Downlight with Trim / Remodel Housing By Eurofase



### Description

The 28719 3 Inch Round Aperture Non-IC Remodel Housing with Downlight Trim is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes 15 watt, 120-277V LED module with 40 degree beam angle in 3000K or 3500K color temperature, 90+CRI, up to 1049 delivered lumens. 50,000 hour average lamp life. ERP 3-in-1 dimmable driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Cutout: 3.25 inch round. TRIAC and ELV dimming at 120V. 0-10V dimming at 277V. Non-IC new construction mounting plate or IC new construction housing sold separately.

### Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.88"W x 5.75"H
INTEGRATED LED MODULE	1 x LED/15W/120-277V LED
COUNTRY OF ORIGIN	China

### Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Round
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	69.93
LUMINOUS FLUX	1049 lumens



Shown in black



CLICK TO VIEW PRODUCT

Notes: