



BRAND

Eurofase

DESCRIPTION

The 28720 3 Inch Round Aperture Non-IC Remodel Housing with Gimbal Adjustable Trim is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 2700K or 3000K color temperature, 80+ CRI, 1290 lumens. 30 degree tilt. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC (low voltage electronic) dimmer, sold separately. Cutout: 3.25 inch round. Can be converted to a Non-IC new construction housing using the 30534-018 mounting plate.





Shown in: White

TRIM COLOR	N/A
BODY FINISH	White
WATTAGE	15W
DIMMER	Standard 120V
DIMENSIONS	3.88"W x 5.75"H
INTEGRATED LED MODULE	
LAMP	1 x LED/15W/120V LED

Technical Information

LUMINOUS FLUX	1290 lumens
LUMENS/WATT	86.00
LAMP COLOR	3000K
COLOR RENDERING	80 CRI
BEAM ANGLE	40°
LAMP LIFE	50000 hours
FUNCTION	Adjustable Accent
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC
HOUSING HEIGHT	6"
SPEC #	EUF543238



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE