

Lightology

lightology.com
866-954-4489
04-15-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EUF543238**
 Approved On: _____ Approved By: _____

Amigo 3IN RD Adjustable Gimbal Trim / Remodel Housing By Eurofase



Description

The 28720 3 Inch Round Aperture Non-IC Remodel Housing with Gimbal Adjustable Trim is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 2700K or 3000K color temperature, 80+CRI, 1290 lumens. 30 degree tilt. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC (low voltage electronic) dimmer, sold separately. Cutout: 3.25 inch round. Can be converted to a Non-IC new construction housing using the 30534-018 mounting plate.

Specifications



REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White
WATTAGE	15W
DIMMER	Standard 120V
DIMENSIONS	3.88"W x 5.75"H
INTEGRATED LED MODULE	1 x LED/15W/120V LED
COUNTRY OF ORIGIN	China

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Round
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	80 CRI
LAMP COLOR	3000K
LUMENS/WATT	86.00
LUMINOUS FLUX	1290 lumens



Shown in white



CLICK TO VIEW PRODUCT

Notes: