




BRAND

Eurofase

DESCRIPTION

The 28721 3 Inch Square Aperture Non-IC Remodel Housing with Downlight Trim is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 3000K or 3500K color temperature, 80+CRI, 1290 lumens. 50,000 hour average lamp life. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC dimmer, sold separately. Cutout: 3.25 inch square. Can be converted to a Non-IC new construction housing using the 30535-15 mounting plate.





Shown in: Black

TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	15W
DIMMER	Standard 120V
DIMENSIONS	3.88"W x 5.75"H x 3.88"D
LED MODULE INCLUDED	
LAMP	1 x LED/15W/120V LED

Technical Information

LUMINOUS FLUX	1290 lumens
LUMENS/WATT	86.00
LAMP COLOR	3000 K
COLOR RENDERING	80 CRI
BEAM ANGLE	40°
LAMP LIFE	50000 hours
FUNCTION	Downlight
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC
HOUSING HEIGHT	6"
ITEM NUMBER	EUF543243



3 1/4"L X 3 1/4"W

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE