

# Lightology

lightology.com  
866-954-4489  
04-16-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **EUF543243**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Amigo 3IN SQ Downlight Trim / Remodel Housing By Eurofase



### Description

The 28721 3 Inch Square Aperture Non-IC Remodel Housing with Downlight Trim is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes 15 watt, 120 volt LED module with 40 degree beam angle in 3000K or 3500K color temperature, 80+CRI, 1290 lumens. 50,000 hour average lamp life. Class 2 dimmable constant current driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Input voltage: 120 volt. Dimmable with a TRIAC dimmer, sold separately. Cutout: 3.25 inch square. Can be converted to a Non-IC new construction housing using the 30535-15 mounting plate.

### Specifications


REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	15W
DIMMER	Standard 120V
DIMENSIONS	3.88"W x 5.75"H x 3.88"D
INTEGRATED LED MODULE	1 x LED/15W/120V LED
COUNTRY OF ORIGIN	China

### Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	80 CRI
LAMP COLOR	3000K
LUMENS/WATT	86.00
LUMINOUS FLUX	1290 lumens



Shown in black



CLICK TO VIEW PRODUCT

Notes: