Lightology

lightology.com
866-954-4489
11-09-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EUF543243**

Approved On: Approved By:

Amigo 3 inch Square Downlight with Trim / Remodel Housing


By Eurofase

Description

The 28721 3 Inch Square Aperture Non-IC Remodel Housing with Downlight Trim is constructed of 18 gauge powder coated steel. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes 15 watt, 120-277 volt LED module with 40 degree beam angle in 3000K or 3500K color temperature, 90+CRI, up to 1049 lumens. 50,000 hour average lamp life. ERP 3-in-1 dimmable driver included. Driver box mates to fixture by 12 inch flexible BX cable. Thermally protected. Cutout: 3.25 inch square.TRIAC and ELV dimming at 120V. 0-10V dimming at 277V. Optional new construction Non-IC mounting plate or new construction IC housing sold separatey.



Shown in black



Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.88"W x 5.75"H x 3.88"D
INTEGRATED LED MODULE	1 x LED/15W/120-277V LED
COUNTRY OF ORIGIN	China

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Square
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim
FUNCTION	Downlight
LAMP LIFE	50000 hours
BEAM ANGLE	40°
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	69.93
LUMINOUS FLUX	1049 lumens

CLICK TO VIEW PRODUCT

Notes: