Lightology

lightology.com
866-954-4489
11-08-26

Project:

Company:

Location: Fixture Type:

SPEC #: **EUF543731**

Approved On: Approved By:

PAR20 LED 2X2 Trim with Remodel Housing

By Eurofase

Description

The TE164BLED 6 Inch Aperture 4-Light Square Non-IC Remodel Housing is constructed of 18 gauge powder coated steel and features adjustable mounting clips suitable for 1/2 inch and 5/8 inch drywall. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes adjustable 4-light trim made of extruded aluminum available in a powder coat White trim with a White or Black reflector, or a powder coat Black trim with a Black reflector. Includes 4X15 watt, 120 volt LED module with 20 or 40 degree beam angle in 3000K, 3500K or 4000K color temperature, 90+CRI, 4X1290 lumens. 50,000 hour average lamp life. 0-20 degree horizontal adjustment. Class 2 dimmable constant current driver included. Driver box mates to fixture by 24 inch flexible BX cable and has one 1/2 inch and two 3/4 inch knockouts for through branch wiring. Dimmable with a TRIAC dimmer, sold separately. ETL listed.



Shown in white trim / white reflector

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	White Trim / White Reflector
WATTAGE	60W
DIMMER	Standard 120V
DIMENSIONS	10.63"W x 6"H x 10.63"D
INTEGRATED LED MODULE	4 x LED/15W/120V LED
COUNTRY OF ORIGIN	China

Technical Information

APERTURE SIZE	6.000"
APERTURE SHAPE	Square
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall with Trim
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	20°
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	344.00
LUMINOUS FLUX	5160 lumens

CLICK TO VIEW PRODUCT

Notes: