

Lightology

lightology.com
866-954-4489
04-25-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **EUF543731**

Approved On: _____ Approved By: _____

PAR20 LED 2X2 Trim with Remodel Housing By Eurofase



Description

The TE164BLED 6 Inch Aperture 4-Light Square Non-IC Remodel Housing is constructed of 18 gauge powder coated steel and features adjustable mounting clips suitable for 1/2 inch and 5/8 inch drywall. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes adjustable 4-light trim made of extruded aluminum available in a powder coat White trim with a White or Black reflector, or a powder coat Black trim with a Black reflector. Includes 4X15 watt, 120 volt LED module with 20 or 40 degree beam angle in 3000K, 3500K or 4000K color temperature, 90+CRI, 4X1290 lumens. 50,000 hour average lamp life. 0-20 degree horizontal adjustment. Class 2 dimmable constant current driver included. Driver box mates to fixture by 24 inch flexible BX cable and has one 1/2 inch and two 3/4 inch knockouts for through branch wiring. Dimmable with a TRIAC dimmer, sold separately. ETL listed.

Specifications

REFLECTOR/BAFFLE COLOR N/A
BODY FINISH White Trim / White Reflector
WATTAGE 60W
DIMMER Standard 120V
DIMENSIONS 10.63"W x 6"H x 10.63"D
INTEGRATED LED MODULE 4 x LED/15W/120V LED
COUNTRY OF ORIGIN China

Technical Information

APERTURE SIZE 6.000"
APERTURE SHAPE Square
HOUSING HEIGHT 6"
HOUSING TYPE Remodel NON IC
CEILING TYPE Drywall with Trim
FUNCTION Adjustable Accent
LAMP LIFE 50000 hours
BEAM ANGLE 20°
COLOR RENDERING 90 CRI
LAMP COLOR 3000K
LUMENS/WATT 344.00
LUMINOUS FLUX 5160 lumens



Shown in white trim / white reflector



CLICK TO VIEW PRODUCT

Notes: