



BRAND

Eurofase

DESCRIPTION

The TE164BLED 6 Inch Aperture 4-Light Square Non-IC Remodel Housing is constructed of 18 gauge powder coated steel and features adjustable mounting clips suitable for 1/2 inch and 5/8 inch drywall. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Includes adjustable 4-light trim made of extruded aluminum available in a powder coat White trim with a White or Black reflector, or a powder coat Black trim with a Black reflector. Includes 4X15 watt, 120 volt LED module with 20 or 40 degree beam angle in 3000K, 3500K or 4000K color temperature, 90+CRI, 4X1290 lumens. 50,000 hour average lamp life. 0-20 degree horizontal adjustment. Class 2 dimmable constant current driver included. Driver box mates to fixture by 24 inch flexible BX cable and has one 1/2 inch and two 3/4 inch knockouts for through branch wiring. Dimmable with a TRIAC dimmer, sold separately. ETL listed.



Shown in: White Trim / White Reflector

TRIM COLOR	N/A
BODY FINISH	White Trim / White Reflector
WATTAGE	60W
DIMMER	Standard 120V
DIMENSIONS	10.63"W x 6.3"H x 10.63"D
INTEGRATED LED MODULE	
LAMP	4 x LED/120V LED

Technical Information

LUMINOUS FLUX	5160 lumens
LUMENS/WATT	344.00
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
BEAM ANGLE	40°
LAMP LIFE	50000 hours
FUNCTION	Adjustable Accent
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC
HOUSING HEIGHT	6"
SPEC #	EUF543735

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE