

lightology.com 866-954-4489 05-01-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>LUT568598</b>	
Approved On:	Approved By:

## Hi-Lume 0.1% EcoSystem 3-Wire Constant Voltage Driver 24V By Lutron



## Description

The Lutron Hi-lume Premier 0.1% Constant Voltage 24V Driver (L3D0) is a high-performance 3-wire LED driver capable of controlling up to 96 watts of 24V-constant voltage loads. Power Input: 120-277V AC, 60Hz. Power Output: Class 2, 24 volts DC 1.67A. The driver is UL Listed with an integrated wiring compartment and can be mounted up to 150 feet away from the load. This driver provides smooth and continuous dimming down to 0.1 percent low-end. It is ideal for use with strip lighting in applications such as coves, under or over cabinet lighting and pathway lighting. Guaranteed dimming performance when used with Lutron controls: HomeWorks QS, Energi Savr Node units with EcoSystem controls, GRAFIK Eye QS with EcoSystem controls, PowPak with EcoSystem dimming modules, PowPak with EcoSystem wireless fixture controls, and Quantum systems, allowing for integration into a planned or existing EcoSystem lighting control solution. Lutron 3-wire controls and interfaces.



Shown in white

## Specifications

COLOR																N,	/A
BODY FINISH															. V	۷hi	te
WATTAGE																96\	N
DIMMER																N,	/Α
DIMENSIONS											10"	W	x 2	2"F	ХŁ	5.5"	D
BULB NOT INCLUDED																N,	/Α
COUNTRY OF ORIGIN															М	exic	co



**CLICK TO VIEW PRODUCT** 

Notes:	