

Lightology

lightology.com
866-954-4489
05-26-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **EDG57682**
 Approved On: _____ Approved By: _____

Sun3C Indoor/Outdoor Ceiling LED Downlight - Discontinued

By PureEdge Lighting



Description



The Sun3C 3 Inch Round or Square LED ceiling recessed downlight is a perfect solution for installations on ceilings with low clearance in indoor and outdoor applications. Must be used only with new construction IC-rating housing (SUN3-HS), sold separately. Features a marine grade aluminum beveled edge trim in Satin Aluminum with a tempered glass lens. Available in 16, 23, 36 and 47 degree beam options. Sun3C is rated for outdoor, ocean front, wet location, shower, or indoor applications. For ceiling recessed applications only. For floor or wall applications use SUN3. A complete fixture requires a Sun3C trim and housing (SUN3-HS), sold separately. Dimmable with a low voltage electronic dimmer (see attached manufacturer dimmer compatibility reference).

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	8.8W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.3"W x 3.3"H
INTEGRATED LED MODULE	1 x LED/8.8W/120V LED

Technical Information

APERTURE SIZE	3.000"
APERTURE SHAPE	Round
FUNCTION	Shower/Wet Location
LAMP LIFE	50000 hours
BEAM ANGLE	36°
COLOR RENDERING	95 CRI
LAMP COLOR	3000K
LUMENS/WATT	73.18
LUMINOUS FLUX	644 lumens



Notes: