

Lightology

lightology.com
866-954-4489
05-17-26

Project: _____

Company: _____

Location: _____ Fixture Type: _____

SPEC #: **ELE614235**

Approved On: _____ Approved By: _____

Element 3IN SQ Flangeless Adjustable Remodel Housing By Visual Comfort Architectural



Description

3 Inch Square 90CRI Adjustable Downlight Remodel Non-IC Housing for use with square flangeless trims. Features precision aiming mechanism with a 0-40 degree tilt, 361 degree rotation, and high-low lamp positioning. Includes LED module in three color temperature options in low output (12 watt) or high output (17 watt) or Warm Dim (3000K-1800K) with 10, 18, 25, 40 or 60 degree beam angle options. Suitable for damp locations. Suitable for wet locations with shower trim option. Includes a 120-277V Universal driver dimmable with standard reverse-phase, forward-phase, TRIAC, and 0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately. Note: Warm Dim option is not available with 10 degree beam angle.

Specifications



REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	17W
DIMMER	Low Voltage Electronic
DIMENSIONS	3.8"W x 5.8"H
INTEGRATED LED MODULE	1 x LED/17W/120-277V LED

Technical Information

APERTURE SHAPE	Square
HOUSING HEIGHT	6"
HOUSING TYPE	Remodel NON IC
CEILING TYPE	Drywall Trimless/Flush
FUNCTION	Adjustable Accent
LAMP LIFE	50000 hours
BEAM ANGLE	10°
COLOR RENDERING	90 CRI
LAMP COLOR	2700K
LUMENS/WATT	86.82
LUMINOUS FLUX	1476 lumens



Shown in black



*SHOWN IN SQUARE FLANGELESS AT FULL TILT (45°)



CLICK TO VIEW PRODUCT

Notes: