



BRAND Visual Comfort Architectural


DESCRIPTION

2 Inch Round Flanged Adjustable Downlight and Wall Wash Non-IC Remodel Housing. Non-IC designation requires that insulation be kept a minimum of 3 inches away from housing. Housing features an integral 12 watt (average 930 lumens) or 17 watt (average 1250 lumens) LED module in three color temperature options with 20, 30, 40 or 60 degree beam angle, or Warm Dim (3000K to 1800K) in low output (12 watt/average 850 lumens) and 20, 30, 40 or 60 degree beam angle. 30 degree optimal for wall wash use. Adjust to 15 degree tilt for wall wash application. Features 0-45 degree tilt, 361 degree rotation, and high-low lamp positioning. Suitable for ceiling thickness up to 2 inches. 2.75 inch ceiling opening. ETL listed. Suitable for damp locations. Suitable for wet locations with shower trim. 5 year warranty. A complete fixture includes a housing and trim sold separately.NOTE: WARM DIM OPTION AVAILABLE IN LOW OUTPUT (12 WATT) ONLY.



Shown in: Black

TRIM COLOR	N/A
BODY FINISH	Black
WATTAGE	17W
DIMMER	Low Voltage Electronic
DIMENSIONS	2.7"W x 4.5"H
INTEGRATED LED MODULE	
LAMP	1 x LED/17W/120V LED
Technical Information	
LUMINOUS FLUX	1250 lumens
LUMENS/WATT	73.53
LAMP COLOR	2700K
COLOR RENDERING	90 CRI
BEAM ANGLE	60°
LAMP LIFE	50000 hours
CEILING TYPE	Drywall with Trim
HOUSING TYPE	Remodel NON IC
HOUSING HEIGHT	6"
SPEC #	ELE614341



COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE