

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>EMR615350</b>	
Approved On:	Approved By:

## Fusion Rectangle Lighted Mirror By Electric Mirror









## Description

The Fusion Lighted Mirror is designed to maximize direct illumination. Ideal for precision tasks such as makeup application and shaving. White powder coated chassis for finished side view. Corrosion resistant DuraMirror glass. Choice of standard control or with Ava dimming. Ava Smart Look technology features tunable white LED lights that allow you to select the color temperature. Select between 6500K for a day of outdoor activities, 4600K for your daily routine, or 2700K for a night out on the town. Tap to Cycle through 2700K, 4600K, 6500K, Night Glow and Off. At every level, hold to dim down to 10%. After one hour of non-use, Energy Save Mode automatically dims lights to 10%. Available in four sizes. Note: The Fusion mirror must be installed in the W x H (width x height) orientation as listed; it cannot be installed in any other direction.

## Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER
DIMENSIONS
INTEGRATED LED MODULE
COUNTRY OF ORIGIN

## Technical Information

LAMP LIFE	 	 	 	 	. 52000 hours
COLOR RENDERING	 	 	 	 	90 CRI
LAMP COLOR	 	 	 	 	3000K
LUMENS/WATT	 	 	 	 	130.39
LUMINOUS FLUX .	 	 	 	 	. 7041 lumens



Shown in mirror



MODELS						
Base Model* Model Type		Dimensions	Initial Lumens/Fixture	Power Requirements		
FUS-2436	Standard	24" W x 36" H x 1.75" D (610mm W x 914mm H x 44mm D)	7,041	120-277VAC, 54W		
FUS-2436-AK	With Ava™		2,930	120 or 277VAC, 39W		
FUS-4836	Standard	48" W x 36" H x 1.75" D (1,219mm W x 914mm H x 44mm D)	7,041	120-277VAC, 54W		
FUS-4836-AK	With Ava**		2,930	120 or 277VAC, 39W		
FUS-6036	Standard	60° W x 36° H x 1.75° D	7,041	120-277VAC, 54W		
FUS-6036-AK	With Ava"	(1,524mm W x 914mm H x 44mm D)	2,930	120 or 277VAC, 39W		



**CLICK TO VIEW PRODUCT** 

Notes:				
--------	--	--	--	--