

# Lightology

lightology.com  
866-954-4489  
05-12-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **WAC617193**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Volta 2 inch Square New Construction IC Airtight Housing By WAC Lighting



### Description


The Volta 2 Inch Square New Construction IC Airtight Housing for use with square flanged trims is available in a 15 watt (10 watt for Spot beam angle) and 22 watt (15 watt for Spot beam angle) option. See trim for lumen output. Includes a Universal 120V-277V AC 50/60Hz driver. ELV dimmable at 120V. ELV or 0-10V dimmable at 120/277V. Note: A complete fixture requires a housing and trim, sold separately.



Shown in black

\*Power consumption depends on beam angle of the trim.

Model	Power*	S	N, F, W, A
Square New Construction R25NT Airtight	15	10W	15W
	22	15W	22W



### Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Black
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	18.12"W x 5.5"H x 9.94"D
BULB NOT INCLUDED	1 x LED/15W/120-277V LED

### Technical Information

APERTURE SIZE	2.000"
APERTURE SHAPE	Square
HOUSING HEIGHT	6"
HOUSING TYPE	New construction IC Airtight
CEILING TYPE	Drywall with Trim



CLICK TO VIEW PRODUCT

Notes: