

lightology.com 866-954-4489 08-20-25

| Project: | |
|--------------------------|---------------|
| Company: | |
| Location: | Fixture Type: |
| SPEC #: EDG621440 | |
| Approved On: | Approved By: |

Zipp Wave Linear Suspension/Remote Power/2IN Round Canopy By PureEdge Lighting





Description

Add angles and dimensions to any space with the Zipp Wave Suspension Downlight with End Feed Canopy. Available with a 2 inch round canopy in a range of increments from 48 to 240 inches and features a white lens with 100 degree beam spread, optional adjustable white or black louver, multiple finishes, and a spectrum of color temperatures. Product is built to order. Note: Canopy mounts to a standard junction box either using the PS-60L-ELV-24VDC (60 Watt 24 Volt DC Power Supply) which fits inside junction box, or from a 24VDC remote Universal (UNI) power supply. Universal dimming with UNI power supply (TRIAC/ELV/0-10V). ELV dimming with PS-60L-ELV power supply. Power supply, dimmer control, and optional accessories sold separately. Note: Includes a 2.8 inch round canopy and adjustable 12 foot coaxial and aircraft cables. Additional aircraft cables are included for support when fixture exceeds 96 inches.


Specifications

| COLOR | | | | | | | | | |
|-------------------------------|--|--|--|--|--|--|--|--|--|
| BODY FINISH Satin Nickel | | | | | | | | | |
| WATTAGE | | | | | | | | | |
| DIMMER Low Voltage Electronic | | | | | | | | | |
| DIMENSIONS | | | | | | | | | |
| INTEGRATED LED MODULE | | | | | | | | | |
| | | | | | | | | | |
| Technical Information | | | | | | | | | |

| LAMP LIFE | | | | | | | | | | | | | 50000 hours |
|------------|--------|--|--|--|--|--|--|--|--|--|--|--|---------------|
| COLOR REN | DERING | | | | | | | | | | | | 95 CRI |
| LAMP COLO | R | | | | | | | | | | | | 2700K |
| LUMENS/WA | ATT | | | | | | | | | | | | 211.00 |
| LUMINOUS F | LUX . | | | | | | | | | | | | . 1055 lumens |



Shown in satin nickel / white lens





CLICK TO VIEW PRODUCT

| Notes: | | | |
|--------|--|--|--|
| | | | |