



BRAND

Generation Lighting

DESCRIPTION

Traverse LED Lyte Downlight is designed for superior performance and value. This surface-mounted downlight works with all junction boxes and retrofits into most 5 inch and 6 inch recessed housings with adaptor for ultimate installation flexibility. It offers outstanding energy efficiency with 750- 800 delivered lumens of light output generated, while consuming a minimal amount of energy. The 6 inch round aperture hugs the ceiling surface. Available with a White or Satin Nickel trim. Dimmable to 5% with low-voltage electronic or Triac dimmers (see dimming chart). Wet location listed for shower ceiling installations.



TRIM COLOR	N/A
BODY FINISH	White
WATTAGE	13W
DIMMER	Low Voltage Electronic
DIMENSIONS	7.38"W x 1.06"H
INTEGRATED LED MODULE	
LAMP	1 x LED/13W/120V LED

Technical Information

LUMINOUS FLUX	750 lumens
LUMENS/WATT	57.69
LAMP COLOR	3000K
COLOR RENDERING	90 CRI
LAMP LIFE	50000 hours
HOUSING TYPE	Retro kit
APERTURE SHAPE	Round

SPEC #	SGL624807
--------	-----------

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE