

# Lightology

lightology.com  
866-954-4489  
04-29-26

Project: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
 SPEC #: **EDG625038**  
 Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Verge Wall Warm Dim Plaster-In System By PureEdge Lighting



### Description

Verge Wall Warm Dim is a slim, plaster-in aluminum channel with 4 inch paintable aluminum backer plate. Verge Wall creates and highlights the transition space where two drywall surfaces join together while emitting ambient illumination. Verge Warm Dim Wall is sold in 5 foot increments up to 40 feet and may be field cut to any length. Available in Warm Dim 27D (2700-1800K) or 30D (3000-1800K) color temperature. Verge requires a Universal (UNI) power supply, sold separately. UNI power supply compatible with TRIAC, ELV and 0-10V dimming. Required power supply, dimmer control, and optional accessories sold separately. Product is built to order. Included Components: Junction Box, Adjustable Mounting Bars, Backer Plate, Verge Wall Channel(s), Drywall Screws, LED Strip, and Lens(es)

### Specifications


COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	60"L x 0.75"W x 4"H
INTEGRATED LED MODULE	5 x LED/5W/24V LED

### Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	92 CRI
LAMP COLOR	2700K Warm Dim
LUMENS/WATT	744.00
LUMINOUS FLUX	3720 lumens



#### INCLUDED COMPONENTS



- A. JUNCTION BOX**  
Mounts behind channel with Adjustable Mounting Bars. Low Voltage 24VDC wires from Remote Power Supply connect to the wires inside box. Junction Box opening is covered by the Backer Plate and secured at the beginning of each channel.
- B. ADJUSTABLE MOUNTING BARS**  
Provide flexibility for mounting in a variety of spaces.
- C. BACKER PLATE**  
4" paintable aluminum plate that conceals Junction Box and reflects light.
- D. STRIP CHANNEL**  
3/8" deep aluminum housing a single row of LED Strip.
- E. OPTICAL GUIDE**  
Screens channel for optimal view.
- F. LED STRIP**  
Commercial grade White or Dynamic Color Changing LED Strip. See lamp data for the additional details.
- G. LENS**  
3/8" wide diffused lens protects a clean line of light without LED penetration.

Notes: