

# Lightology

lightology.com  
866-954-4489  
12-07-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **EDG625078**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Verge Ceiling Warm Dim Drywall Plaster-In System 24V

By PureEdge Lighting



### Description

Verge Ceiling features an innovative design that recesses within 5/8 inch drywall without joist modification. The plaster-in aluminum extrusion features a 4 inch paintable backer plate and highlights ceiling perimeters while emitting smooth and continuous ambient illumination. Available in 1 foot increments (sold in 5 foot increments) up to 20 feet and is field-cuttable. Includes 5 LED watt per foot of Warm Dim 27D (2700K-2200K) or 30D (3000K-2200K) color temperature LED Soft Strip. Included Components: Junction Box, Adjustable Mounting Bars, Backer Plate, Verge Ceiling Channel(s), Drywall Screws, LED Soft Strip and Lens(es). A VG-IRE-JBOX rough-in junction box is available to rough-in electrical before drywall installation (included and sold separately). System requires a remote Universal (UNI) power supply, sold separately. Product is built to order. Note: Required power supply, dimmer control, and optional mounting accessories sold separately.

### Specifications

COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	60"L x 0.75"W x 4.13"H
INTEGRATED LED MODULE	5 x LED/5W/24V LED

### Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	92 CRI
LAMP COLOR	2700K Warm Dim
LUMENS/WATT	148.80
LUMINOUS FLUX	744 lumens



Notes: