

Lightology

lightology.com
866-954-4489
12-09-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG625315**
Approved On: _____ Approved By: _____

Verge Ceiling Static White Drywall Plaster-In System 24V

By PureEdge Lighting



Description


Verge Ceiling features an innovative design that recesses within 5/8 inch drywall without joist modification. Available in 1 foot increments (sold in 5 foot increments) up to 40 feet (2 Watt), 20 feet (5 Watt), and 12 feet (7 Watt) and is field-cutable. The plaster-in aluminum extrusion features a 4 inch paintable backer plate and highlights ceiling perimeters while emitting smooth and continuous ambient illumination. Included Components: Junction Box, Adjustable Mounting Bars, Backer Plate, Verge Ceiling Channel(s), Drywall Screws, LED Soft Strip and Lens(es). System requires a remote Universal (UNI) power supply. A VG-1RE-JBOX rough-in junction box is available to rough-in electrical before drywall installation (included and sold separately). Product is built to order. Note: Required power supply, dimmer control, and optional mounting accessories sold separately. MAXIMUM LENGTHS BEFORE RE-FEEDING: 2WDC, 2.5 watts per foot - 40 Feet 5WDC, 4.4 watts per foot - 20 Feet 7WDC, 7.5 watts per foot - 12 Feet

Specifications

COLOR N/A
BODY FINISH Satin Aluminum
WATTAGE 25W
DIMMER Low Voltage Electronic
DIMENSIONS 60"L x 0.75"W x 4.13"H
INTEGRATED LED MODULE 5 x LED/5W/24V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 95 CRI
LAMP COLOR 2700K
LUMENS/WATT 372.00
LUMINOUS FLUX 1860 lumens



Notes: