



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

### DESCRIPTION

Verge Corner features an innovative design that mounts directly to wall studs or ceiling joists without any modification, and is recessed and plastered into 5/8 inch drywall. The Verge system creates visually interesting and dramatic illumination by highlighting the inside corners of two drywall surfaces. Sold in 1 foot increments up to 20 feet (10 feet with 10 watt) and is field-cuttable. Features a 4 inch paintable backer plate. System may be controlled with a Universal (UNI) or Lutron Hi-Lume power supply, sold separately. Included components: Verge Corner Channels, Junction Boxes, Adjustable Mounting Bars, Backer Plates, Drywall Screws, LED Soft Strip, and Lens(es). ETL listed. Title 24 compliant when used with a Universal (UNI) power supply. Includes a 5-year pro-rated warranty. Required power supply, dimmer control, and optional accessories sold separately.



Shown in: Aluminum

SHADE COLOR	N/A
BODY FINISH	Aluminum
LAMP	5 x LED/5W/24V LED
WATTAGE	25W
DIMMER	Low Voltage Electronic
DIMENSIONS	60"L x 0.75"W x 4"H


#### Technical Information

LUMINOUS FLUX	3720 lumens
LUMENS/WATT	744.00
LAMP COLOR	2700 K
COLOR RENDERING	95 CRI

PRODUCT NUMBER EDG625675



#### INCLUDED COMPONENTS



- A. JUNCTION BOX**  
Mounts behind drywall with Adjustable Mounting Bars, Low Voltage 24VDC wires from Remote Power Supply connected to LED wires inside box. Junction Box opening is covered by the Backer Plate, and required at the beginning of each run.
- B. ADJUSTABLE MOUNTING BARS**  
Provide flexibility for mounting in a variety of spaces. Verge Corner includes two sets of mounting hardware.
- C. BACKER PLATE**  
4" paintable aluminum plates conceal junction box and reflect light.
- D. VERGE CHANNEL**  
Two 5/8" deep extrusions each house a single row of LED Soft Strip.
- E. DRYWALL SCREWS**  
Secure channels to drywall and studs.
- F. LED SOFT STRIP**  
Commercial grade White or Dynamic Color Changing LED Soft Strip. See lamp data on file for additional details. Operated Color Temperatures 2700-6500K, Warm Dim (SDS or SWS), Dynamic/Tunable White (DMW), RGB, and RGBW.
- G. LENS**  
0.5" wide Diffused White lens projects a clean line of light without LED dots. Verge Corner includes two lenses.

COMPANY	PROJECT	FIXTURE TYPE	APPROVED BY	DATE