

lightology.com 866-954-4489 12-28-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG627149	
Approved On:	Approved By:

Glide Glass Up/Down Warm Dim End Feed Suspension By PureEdge Lighting





Description


Glide Glass Up/Down Warm Dim End Feed Suspension is a linear LED fixture that offers direct and indirect light in a clean, contemporary style. Available with one or two canopies. Downlight features a diffused white lens with 100 degree beam spread and optional black or white louvers for adjustability. Uplight features a clear frosted 60 degree lens. Glass available in White, Black or Mirror. Channel widths sold in 12 inch increments from 36 to 120 inches with 10 watts (5 watts up/5 watts down) per foot. Supplied with 12 feet of adjustable coaxial cables (fixtures exceeding 96 inch include additional aircraft cables). Available in 27D (2700K to 2000K) and 30D (3000K to 2000K) Warm Dim color temperatures. 120 volt input, 24VDC Class 2 output, electronic low voltage LED power supply included in canopy. Dimmable with an electronic low voltage dimmer: (Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600 and Lutron Radio Ra 2, or Legrand Adorne ADTP703TU), sold separately. ETL listed. Made in USA. 5 year warranty. Product is built to order.

Specifications


COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

LAMP LIFE		 	50000 hours
COLOR RENDERIN	1G	 	
LAMP COLOR		 	2700K Warm Dim
LUMENS/WATT .		 	170.70
LUMINOUS FLUX		 	1707 lumens



Shown in white glass / no louver





CLICK TO VIEW PRODUCT

Notes: