

### BRAND

PureEdge Lighting

### DESCRIPTION

Glide Glass Up/Down Warm Dim End Feed Suspension is a linear LED fixture that offers direct and indirect light in a clean, contemporary style. Available with one or two canopies. Downlight features a diffused white lens with 100 degree beam spread and optional black or white louvers for adjustability. Uplight features a clear frosted 60 degree lens. Glass available in White, Black or Mirror. Channel widths sold in 12 inch increments from 36 to 120 inches with 10 watts (5 watts up/5 watts down) per foot. Supplied with 12 feet of adjustable coaxial cables (fixtures exceeding 96 inch include additional aircraft cables). Available in 27D (2700K to 2000K) and 30D (3000K to 2000K) Warm Dim color temperatures. 120 volt input, 24VDC Class 2 output, electronic low voltage LED power supply included in canopy. Dimmable with an electronic low voltage dimmer: (Lutron Diva DVELV-300P, Lutron Skylark SELV-300P, Lutron Maestro MAELV-600 and Lutron Radio Ra 2, or Legrand Adorne ADTP703TU), sold separately. ETL listed. Made in USA. 5 year warranty. Product is built to order.



Shown in: White Glass / No Louver


SHADE COLOR	No Louver
BODY FINISH	White Glass
WATTAGE	30W
DIMMER	Low Voltage Electronic
DIMENSIONS	36"L x 1.74"W x 2.5"H
INTEGRATED LED MODULE	
LAMP	3 x LED/120V LED

#### Technical Information

LUMINOUS FLUX	1707 lumens
LUMENS/WATT	170.70
LAMP COLOR	2700K Warm Dim
COLOR RENDERING	92 CRI

SPEC #

EDG627517



CANOPY COVER		
Version	6" Coverage (Surface Mount)	6" Coverage (Surface Mount)
10' (3' x 10')	up to 100'	50'
100' (3' x 10')	up to 100'	50'

COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE