

Lightology

lightology.com
866-954-4489
08-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG628878**
Approved On: _____ Approved By: _____

Glide Wood Up/Down Warm Dim Center Feed Suspension

By PureEdge Lighting



Description

Glide Wood Warm Dim Up/Down Center Feed Linear Suspension is a two-circuit system featuring both direct and indirect LED light. Available in 27D (2700K to 2000K) and 30D (3000K to 2000K) Warm Dim color temperature options with 10 LED watts per foot (5 watts up and 5 watts down). Offered in 12 inch increments from 36 to 120 inches. Available in Walnut, Cherry, White Oak, Espresso or Maple wood finish with 100 degree diffused white downlight lens, 60 degree clear frosted uplight lens, and optional black or white louvers. Includes rectangle canopy with 120V input/24VDC output Universal (UNI) LED power supply. Dimmable with an electronic low voltage (ELV), 0-10V, or Triac (magnetic) dimmer, sold separately. Supplied with 12 feet of adjustable coaxial cables (additional aircraft cables added for support when fixture exceeds 72 inch). Note: Product is built to order.

Specifications


COLOR No Louver
BODY FINISH Wood Cherry
WATTAGE 30W
DIMMER Low Voltage Electronic
DIMENSIONS 36"L x 1.74"W x 2.5"H
INTEGRATED LED MODULE 3 x LED/10W/120V LED

Technical Information

LAMP LIFE 50000 hours
COLOR RENDERING 92 CRI
LAMP COLOR 3000K Warm Dim
LUMENS/WATT 170.70
LUMINOUS FLUX 1707 lumens



Shown in wood cherry / no louver



CLICK TO VIEW PRODUCT

Notes: