

lightology.com 866-954-4489 11-06-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: <b>EDG628878</b>	
Approved On:	Approved By:

## Glide Wood Up/Down Warm Dim Center Feed Suspension By PureEdge Lighting









## Description


Glide Wood Warm Dim Up/Down Center Feed Linear Suspension is a two-circuit system featuring both direct and indirect LED light. Available in 27D (2700K to 2000K) and 30D (3000K to 2000K) Warm Dim color temperature options with 10 LED watts per foot (5 watts up and 5 watts down). Offered in 12 inch increments from 36 to 120 inches. Available in Walnut, Cherry, White Oak, Espresso or Maple wood finish with 100 degree diffused white downlight lens, 60 degree clear frosted uplight lens, and optional black or white louvers. Includes rectangle canopy with 120V input/24VDC output Universal (UNI) LED power supply. Dimmable with an electronic low voltage (ELV), 0-10V, or Triac (magnetic) dimmer, sold separately. Supplied with 12 feet of adjustable coaxial cables (additional aircraft cables added for support when fixture exceeds 72 inch). Note: Product is built to order.

## Specifications COLOR . . . . .

BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE
Technical Information
LAMP LIFE
COLOR RENDERING
LAMP COLOR



Shown in wood cherry / no louver





CLICK TO VIEW PRODUCT

Notes: