

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG635767	
Approved On:	Approved By:

Light Channel .6 Warm Dim Surface Mount By PureEdge Lighting









Description

The Light Channel .6 Warm Dim Surface Mount is a slim profile made to order channel designed to enhance spaces with depth and dimension, seamlessly integrating into the architecture while delivering premium task lighting.. Channel is available in 12 inch increments up to 120 inches with a diffused white lens (projects clean lights of light eliminating pixelation) or a clear lens (LED diodes will show) for maximum light levels. Available in a 5 watt (4.8 watts) per foot option with Warm Dim 27D (2700K-1800K) or 30D (3000K-2000K) color temperature. Warm Dim technology mimics an incandescent atmosphere by decreasing the color temperature as you dim. Included components: Light Channel Surface Mount Assembly, 24VDC LED Strip, 96 inch power connector (one per fixture), mounting clips (included with every 2 feet of channel), lens, lever nuts and end caps. System requires a 50 watt (PS-60L-ELV) ELV power supply which fits inside junction box (dimmable with ELV), or a remote Universal (UNI) power supply (dimmable with ELV/ TRIAC/0-10V). Note: Required power supply, dimmer control, and optional mounting accessories sold separately.


Specifications

COLOR
BODY FINISH
WATTAGE
DIMMER Low Voltage Electronic
DIMENSIONS
INTEGRATED LED MODULE

Technical Information

LAMP LIFE
COLOR RENDERING
LAMP COLOR
LUMENS/WATT
LUMINOUS FLUX

Shown in satin aluminum / diffused lens





CLICK TO VIEW PRODUCT

Notes:
