

Lightology

lightology.com
866-954-4489
07-05-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **EDG635813**
Approved On: _____ Approved By: _____

Light Channel .6 5W Surface Mount - Overstock

By PureEdge Lighting



Description


The Light Channel .6 Surface Mount is a slim profile channel available in Satin Aluminum with a white diffuser lens (eliminates LED dots). Includes a 5 watt per foot LED module with 3000K color temperature. A remote electronic low voltage (ELV) power supply is required. The PS-60L-ELV-24VDC power supply will fit inside junction box. Included components: Light Channel .6 Surface Mount, 96 inch solderless Snap & Light Power Connector (one per fixture), 24VDC LED Soft Strip, Light Channel .6 Surface Mount Assembly, mounting clips (included with every 2 feet of channel), end caps, lens, and a 96 inch power cord. ETL listed. 5 year warranty. Product is built to order. Required power supply, dimmer control, and optional mounting accessories sold separately.

Specifications


COLOR	N/A
BODY FINISH	Satin Aluminum
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	34"L x 0.75"W x 0.37"H
INTEGRATED LED MODULE	3 x LED/5W/120V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	3000K
LUMENS/WATT	112.20
LUMINOUS FLUX	561 lumens



Components: Light Channel .6 Surface Mount system overview



- A. Light Channel .6 Surface Mount (Included Component)
- B. End Caps (Included Component)
- C. Light Channel Power Connector (Included Component)
- D. Lens (Included Component)
- E. Light Channel .6 Surface Mount Assembly
- F. 24VDC LED Strip (Included Component)
- G. Lens (Included Component)
- H. Mounting Clips (Included Component with every 2' of channel)
- I. Remote Power Supply (Sold Separately)

Notes: