

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG648091	
Approved On:	Approved By:

Light Channel .6 Warm Dim Surface Mount Micro Grazer By PureEdge Lighting









Description

The Light Channel .6 Warm Dim Micro Grazer is a slim profile made-to-order channel designed to bring life to textured walls, panels, masonry and undulating tiles. The Micro Grazer is available in 12 inch increments up to 120 inches with a 20 degree linear frosted lens (projects some pixelation) or a clear 7 degree transparent clear lens (LED diodes will show) for maximum light levels. Available in a 5 watts (4.8 watts) per foot option with Warm Dim 27D (2700K-1800K) or 30D (3000K-2000K) color temperature. Warm Dim technology mimics an incandescent atmosphere by decreasing the color temperature as you dim. Included components: Light Channel Micro Grazer Assembly, 96 inch Power Connector (one per fixture), 24VDC LED Soft Strip, mounting clips (included with every 2 feet of channel), end caps, lever nuts, and lens.A PS-60L-ELV-24VDC (50 watt ELV power supply will fit inside a standard junction box), or a remote Universal power supply is required and sold separately. Note: Required power supply, dimmer control, and optional mounting accessories sold separately.


Specifications

BODY FINISH						
WATTAGE						
DIMMER Low Voltage Electronic						
DIMENSIONS						
INTEGRATED LED MODULE						
Technical Information						
LAMP LIFE						
COLOR RENDERING						

 LUMENS/WATT
 48.40

 LUMINOUS FLUX
 242 lumens

Shown in satin aluminum / clear lens





CLICK TO VIEW PRODUCT

Notes:					
--------	--	--	--	--	--