

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG653096	
Approved On:	Approved By:

Glide Wood Downlight Suspension w/ End Feed Power By PureEdge Lighting



Description

Glide Wood Downlight Suspension with End Feed Power is a linear LED fixture that offers direct light in a clean, contemporary style. Available with one or two canopies. Genuine hand-finished hardwood available in Walnut, Cherry, Maple, White Oak or Espresso featuring a diffused white lens with 100 degree beam spread, optional black or white louvers, a variety of finishes, three wattage options, and a spectrum of color temperature options. Channel lengths sold in 12 inch increments from 36 to 120 inches. Canopy size dependent on fixture length. 4 inch canopy available in Satin Nickel for Maple, Walnut, Cherry, and White Oak. Wood Espresso is paired with a Black canopy. Refer to canopy chart for corresponding lengths and canopy finishes. Supplied with 12 feet of adjustable coaxial cables (fixtures exceeding 72 inch include additional aircraft cables). 120 volt input, 24VDC Class 2 output, electronic low voltage LED power supply included in canopy. Dimmable with an electronic low voltage dimmer, sold separately. ETL listed. 5 year warranty. Product is built to order.

Specifications


COLOR			 	 	No Louver
BODY FINISH .			 	 	Wood Walnut
WATTAGE			 	 	15W
DIMMER			 	 	. Low Voltage Electronic
DIMENSIONS .			 	 	36"L x 1.74"W x 2.5"H
INTEGRATED LED	MOD	ULE .	 	 	3 x LED/5W/120V LED

Technical Information

LAMP LIFE												ļ	50000 hours
COLOR RENDERIN	Ĵ.												95 CRI
LAMP COLOR													2700K
LUMENS/WATT .													147.00
LUMINOUS FLUX													735 lumens



Shown in wood walnut / no louver





CLICK TO VIEW PRODUCT

Notes: