

lightology.com 866-954-4489 11-07-25

Project:	
Company:	
Location:	Fixture Type:
SPEC #: EDG655606	
Approved On:	Approved By:

Glide Wood Warm Dim Downlight Suspension w/ End Feed Power By PureEdge Lighting





Description

Glide Wood Warm Dim Downlight Suspension with End Feed Power is a linear LED fixture that offers direct light in a clean, contemporary style. Available with one or two canopies. Genuine hand-finished hardwood available in Walnut, Cherry, Maple, White Oak or Espresso featuring a diffused white lens with 100 degree beam spread, a variety of finishes, and optional black or white louvers. Available in Warm Dim 27D (2700K to 2000K) and 30D (3000K to 2000K) color temperatures with 5 LED watts per foot. Channel lengths sold in 12 inch increments from 36 to 120 inches. Canopy size dependent on fixture length. 4 inch canopy available in Satin Nickel for Maple, Walnut, Cherry, and White Oak. Wood Espresso is paired with a Black canopy. Refer to canopy chart for corresponding lengths and canopy finishes. Supplied with 12 feet of adjustable coaxial cables (fixtures exceeding 72 inch include additional aircraft cables). 120 volt input, 24VDC Class 2 output, electronic low voltage LED power supply included in canopy. Dimmable with an electronic low voltage dimmer, sold separately. ETL listed. 5 year warranty. Product is built to order.


Specifications

Technical Information

LAMP LIFE .																50	00	0 h	our	ŝ
COLOR RENDE	RING																	. 95	CR	I
LAMP COLOR													2	270	00	K١	Na	rm	Dim	١
LUMENS/WATT	٠																	. 18	31.20)
LUMINOUS FLU	JX .															9	06	lum	nens	s



Shown in wood walnut / no louver





CLICK TO VIEW PRODUCT

Notes: