


Lightology

lightology.com
866-954-4489
04-27-26

Project: _____
 Company: _____
 Location: _____ Fixture Type: _____
 SPEC #: **OXY666206**
 Approved On: _____ Approved By: _____

Polaris Wall Sconce

By Oxygen by Quorum



Description

The Polaris Wall Sconce combines a tall rectangular acrylic diffuser with steel housing for a polished, modern look. The emergency backup option includes a backup battery with a 90 minute run time and 32 hour recharge time. This backup option is ETL listed, and the option without emergency backup is UL listed. 120-277V: dimmable with a 0-10V dimmer. 120V: TRIAC or ELV dimmer.

Specifications


COLOR	Matte White
BODY FINISH	Satin Nickel
WATTAGE	12.1W
DIMMER	Low Voltage Electronic
DIMENSIONS	5.75"W x 20.5"H x 4"D
INTEGRATED LED MODULE	1 x LED/12.1W/120-277V LED
COUNTRY OF ORIGIN	China

Technical Information

LAMP LIFE	60000 hours
COLOR RENDERING	90 CRI
LAMP COLOR	3000K
LUMENS/WATT	86.20
LUMINOUS FLUX	1043 lumens



Shown in satin nickel / matte white



W: 5.75"
 H: 20.50"
 Ext: 4.00"
 M.C: 11.25" From top of fixture



CLICK TO VIEW PRODUCT

Notes: