

Lightology

lightology.com
866-954-4489
07-04-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **NOR676353**
Approved On: _____ Approved By: _____

Iolite 2IN Remodel IC Air-Tight Housing By Nora Lighting



Description

The Iolite 2 Inch Remodel IC Air-Tight Housing features steel construction designed for use in insulated ceilings allowing direct contact with thermal insulation. The Iolite is a modular system allowing users to field change both the trim and beam spread without the use of tools. Spot, narrow flood and flood reflectors are included with each trim module. Compatible with 800 lumen and 1000 lumen LED modules. 3.25 inch ceiling cutout. Wet location suitable with compatible trims. Includes a 120-277V power supply with TRIAC/ELV/0-10V dimming. Note: A complete fixture requires a housing and trim, sold separately.

Specifications



REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Steel
WATTAGE 14W
DIMMER Low Voltage Electronic
DIMENSIONS 10"W x 4.88"H
BULB NOT INCLUDED 1 x LED/14W/120-277V LED

Technical Information

APERTURE SIZE 2.000"
HOUSING HEIGHT 5"
HOUSING TYPE Remodel IC
LUMENS/WATT 71.43
LUMINOUS FLUX 1000 lumens



Shown in steel



CLICK TO VIEW PRODUCT

Notes: