

# Lightology

lightology.com  
866-954-4489  
08-30-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **NOR676354**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Iolite 4IN Remodel IC Air-Tight Housing

By Nora Lighting





### Description

The Iolite 4 Inch Remodel IC Air-Tight Housing features steel construction designed for use in insulated ceilings allowing direct contact with thermal insulation. The Iolite is a modular system allowing users to field change both the trim and beam spread without the use of tools. 20, 40 and 60 degree reflectors are included with each trim module. 4.25 inch ceiling cutout. 120/277V. Dimming module: 120 volt TRIAC, 120 volt 0-10V, or 277 volt 0-10V dimming. See attached manufacturer reference for dimmer compatibility. A complete fixture includes a housing and trim, sold separately.



Shown in steel



### Specifications

REFLECTOR/BAFFLE COLOR . . . . . N/A  
BODY FINISH . . . . . Steel  
WATTAGE . . . . . 14W  
DIMMER . . . . . Dimmable  
DIMENSIONS . . . . . 13"W x 6.25"H x 4.25"D  
BULB NOT INCLUDED . . . . . 1 x LED/14W/120V LED

### Technical Information

APERTURE SIZE . . . . . 4.000"  
HOUSING HEIGHT . . . . . 7"  
HOUSING TYPE . . . . . Remodel IC  
LUMENS/WATT . . . . . 5714  
LUMINOUS FLUX . . . . . 800 lumens



CLICK TO VIEW PRODUCT

Notes: