

Lightology

lightology.com
866-954-4489
07-05-25

Project: _____
Company: _____
Location: _____ Fixture Type: _____
SPEC #: **NOR676801**
Approved On: _____ Approved By: _____

Iolite 1IN New Construction IC Housing

By Nora Lighting



Description

The Iolite 1 Inch New Construction IC Air-Tight Housing features aluminum construction for use in insulated ceilings allowing direct contact with thermal insulation. The Iolite is a modular system allowing users to field change both the trim and beam spread without the use of tools. 20, 40 and 60 degree reflectors are included with each trim module. Includes 120/277V electronic driver/power supply mounted in junction box cover. 2.18 inch cutout. Two dimming module options: LE3=120 volt TRIAC dimming. LE4=120 volt 0-10V or 277 volt 0-10V dimming. See attached manufacturer reference for dimmer compatibility. A complete fixture includes a housing and trim, sold separately.



Shown in aluminum

Specifications

REFLECTOR/BAFFLE COLOR N/A
BODY FINISH Aluminum
WATTAGE 11W
DIMMER Low Voltage Electronic
DIMENSIONS 12"W x 4.5"H x 7.75"D
BULB NOT INCLUDED 1 x LED/11W/120V LED

Technical Information

APERTURE SIZE 2.000"
HOUSING HEIGHT 5"
HOUSING TYPE New construction IC Airtight
LUMENS/WATT 72.73
LUMINOUS FLUX 800 lumens



CLICK TO VIEW PRODUCT

Notes: