

# Lightology

lightology.com  
866-954-4489  
07-06-25

Project: \_\_\_\_\_  
Company: \_\_\_\_\_  
Location: \_\_\_\_\_ Fixture Type: \_\_\_\_\_  
SPEC #: **NOR676804**  
Approved On: \_\_\_\_\_ Approved By: \_\_\_\_\_

## Iolite 2IN New Construction IC Airtight Housing

By Nora Lighting



### Description

The Iolite 2 Inch New Construction IC Air-Tight Housing features aluminum construction for use in insulated ceilings allowing direct contact with thermal insulation. The Iolite is a modular system allowing users to field change both the trim and beam spread without the use of tools. Spot, narrow flood and flood field changeable reflectors are included with each trim module. Available with a 120V power supply (TRIAC and ELV dimming), or 120/277V power supply (TRIAC/ELV/0-10V dimming). Compatible with both 800 lumen and 1000 lumen LED modules. Wet location suitable when used with compatible wet location trim. Note: A complete fixture requires a housing and trim with flange or trimless trim, sold separately.

### Specifications



REFLECTOR/BAFFLE COLOR . . . . . N/A  
BODY FINISH . . . . . Aluminum  
WATTAGE . . . . . 14W  
DIMMER . . . . . Low Voltage Electronic  
DIMENSIONS . . . . . 12.5"W x 4.5"H x 7.75"D  
BULB NOT INCLUDED . . . . . 1 x LED/14W/120-277V LED

### Technical Information

APERTURE SIZE . . . . . 2.000"  
HOUSING HEIGHT . . . . . 4"  
HOUSING TYPE . . . . . New construction IC Airtight  
LUMENS/WATT . . . . . 71.43  
LUMINOUS FLUX . . . . . 1000 lumens



Shown in aluminum



CLICK TO VIEW PRODUCT

Notes: