Lightology

lightology.com
866-954-4489
11-07-26

Project:

Company:

Location: Fixture Type:

SPEC #: **NOR676806**

Approved On: Approved By:

Iolite 4IN New Construction IC Housing


By Nora Lighting


Description

The Iolite 4 Inch New Construction IC Air-Tight Housing features aluminum construction for use in insulated ceilings allowing direct contact with thermal insulation. The Iolite is a modular system allowing users to field change both the trim and beam spread without the use of tools. 20, 40 and 60 degree reflectors are included with each trim module. Includes 120/277V electronic driver/ power supply mounted in junction box cover. 4.25 inch cutout. Two dimming module options: LE3=120 volt TRIAC/ELV dimming. LE4= 120-277 volt with TRIAC/ELV dimming at 120V and 0-10V dimming at 277V. Note: A complete fixture requires a housing and trim with flange or trimless trim, sold separately.



Shown in aluminum





CLICK TO VIEW PRODUCT

Specifications

REFLECTOR/BAFFLE COLOR	N/A
BODY FINISH	Aluminum
WATTAGE	14W
DIMMER	Low Voltage Electronic
DIMENSIONS	12"W x 4"H x 7.63"D
INTEGRATED LED MODULE	1 x LED/14W/120V LED

Technical Information

APERTURE SIZE	4.000"
HOUSING HEIGHT	5"
HOUSING TYPE	New construction IC Airtight
LUMENS/WATT	71.43
LUMINOUS FLUX	1000 lumens

Notes: