



DESIGNER

Gregory Kay

BRAND

PureEdge Lighting

DESCRIPTION

Pipeline 1 Warm Dim Up or Down Suspension with End Power Feed and Two Canopies is a linear LED fixture with a clean and contemporary style. Rotates 360 degrees allowing you to shine the light up for indirect light or downward to accommodate task lighting (or anywhere in between). Pipeline 1 is available in various increments from 36 to 240 inches and features a 176 degree beam spread, a diffused white lens, optional black or white louver, 4.4 LED watts per foot, a variety of finishes, and Warm Dim 2700K to 2000K (27D) or 3000K to 2000K (30D) color temperature. Chrome finish available up to 84 inch length. Lengths over 96 inches ship in two segments. Includes two canopies with 120V/24VDC Universal (UNI) LED power supply (dimnable with a Triac (magnetic), electronic low voltage (ELV), or 0-10V dimmer), dimmer sold separately. Only one canopy contains power supply. Power supply wattage and canopy option dependent on fixture length. Supplied with 12 foot adjustable coaxial cables (additional aircraft cables are included for support when fixture exceeds 72 inches). ETL listed. Title 24 compliant. Fixture includes a 5 year warranty. Product is built to order.



Shown in: Satin Nickel / White Lens


SHADE COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	36"L x 1.25"W x 1.25"H
INTEGRATED LED MODULE	
LAMP	3 x LED/5W/120V LED

Technical Information

LUMINOUS FLUX	1242 lumens
LUMENS/WATT	248.40
LAMP COLOR	2700K Warm Dim
COLOR RENDERING	95 CRI

SPEC #

EDG678707



COMPANY

PROJECT

FIXTURE TYPE

APPROVED BY

DATE