

Lightology

lightology.com
866-954-4489
02-18-26

Project:

Company:

Location:

Fixture Type:

SPEC #: EDG681531

Approved On:

Approved By:

Pipeline 1 Power Downlight Suspension Center Feed

By PureEdge Lighting



Description

Pipeline 1 Downlight Suspension with Center Power Feed is a linear LED fixture with a clean and contemporary style. Pipeline 1 is available in various increments from 36 to 120 inches, a diffused white lens with 176 degree beam spread, optional white or black louvers, a variety of finishes, three wattage options, and a spectrum of color temperature options. 84 inch maximum shipping length for Chrome finish. Includes rectangle canopy with 120V input/24VDC Universal (UNI) LED power supply (dimmable with a Triac (magnetic), electronic low voltage (ELV), or 0-10V dimmer), dimmer sold separately. Canopy size dependent on fixture length. Supplied with 12 foot adjustable coaxial cables (additional aircraft cables are included for support when fixture exceeds 72 inches). Note: Product is built to order.

Specifications


COLOR	White Lens
BODY FINISH	Satin Nickel
WATTAGE	15W
DIMMER	Low Voltage Electronic
DIMENSIONS	36" L x 1.25" W x 1.25" H
INTEGRATED LED MODULE	3 x LED/5W/24V LED

Technical Information

LAMP LIFE	50000 hours
COLOR RENDERING	95 CRI
LAMP COLOR	2700K
LUMENS/WATT	197.40
LUMINOUS FLUX	987 lumens



Shown in satin nickel / white lens



CLICK TO VIEW PRODUCT

Notes: